Record of Survey.

No 312

BLK. 49 OF ELKHORN

Township ....., North of Range ROCKWELLS 2ND ADD. of 4 Principal Meridian as presented by the courses and distances on the following plat, and annexed field-notes of survey:

Established the center of the section at the point of intersection of straight quarter lines.

Established all quarter-quarter corners upon the section boundary at proportional distances between known section and quarter section corners, according to the original field-notes of the Government survey.

Established all lost corners at proportionate distances between known corners, according to the original field ~~survey of a government survey~~.

This is to certify that I, [illegible] County Surveyor, Walworth County, Wisconsin, have this day completed a ~~resurvey of a~~ portion of Blk. 49 of Rockwells Second Add. to the Village now City of Elkhorn and set stakes as follows: Establish NE and NW. corners of said blk. and find the distance between said corners to be 266.5 feet. D set iron stake in center being 133.25 feet from either corner, for NW corner of lot 1 of said Block, also set iron stake 66.62 ft. N. of this pt. being 66.62 East of NW corner of Blk.

Var. ° ' Var. ° '

For northeast corner of west half of lot 2, of said Block, d established SE. corner of said block and find distance across each side to be 331.8 feet. D drive iron stake at 165.9 ft. from either corner for southeast corner of lot 4.

Var. ° ' Var. ° '

D find side lines of said block to be parallel with each other and also end lines to be parallel, and so from stake in center of East line, measure West parallel with North line of said block 133.25 feet and drive iron stake for Southwest corner of said lot 4 being center of said block

Var. ° ' Var. ° '

From last mentioned stake measure north parallel with East line of said block 82.9 feet and drive iron stake being 82.9 feet South of center of north line of block. For southeast corner of lot 2. From this last mentioned stake measure west parallel with north line of block 66.62 and set iron stake being 66.62 East of west line. For southeast corner of West half of lot 2 of said block, also set iron stake on west line of blk. 82.9 ft. South of north west corner for southwest corner of lot 2.

Var. ° ' Var. ° '

Surveyed by W. Child C.S.

Recorded by Lloyd S. Jensen C.S.
Feb. 28, 1934

Plat of Section ....., Township ..... North, Range ..... of 4 Principal Meridian Scale 80 chains to 6 inches. The figures in red ink are the lengths of the lines as stated in the field-notes of the Government survey.

Declination of the Magnetic Meridian from the True Meridian .....

Surveyed and sub-divided ..... A. D. 1 , in accordance with the State Laws and Instructions of the Commissioner of the General Land office, and recorded on pages ..... of Register in the County Clerk's office.

Witness my hand this ..... day of ..... A. D. 1

..... SURVEYOR.

DESCRIPTION

OF SECTION, QUARTER SECTION AND QUARTER QUARTER SECTION CORNERS

H. C. MILLER CO., MFG. STATIONERS, MILWAUKEE X15000

GOVERNMENT CORNERS	Bearing Trees	In. Dia.	Courses they bear	Links Distant	Bearing Trees	In. Dia.	Courses they bear	Links Distant	Bearing Trees	In. Dia.	Courses they bear	Links Distant	Bearing Trees	In. Dia.	Courses they bear	Links Distant
No.																
1. N. W. Sec. Cor. indentified,																
2. N. E. Sec. Cor. indentified,																
3. S. E. Sec. Cor. indentified,																
4. S. W. Sec. Cor. indentified,																
5. N. ¼ Sec. Cor. indentified,																
6. E. ¼ Sec. Cor. indentified,																
7. S. ¼ Sec. Cor. indentified,																
W. ¼ Sec. Cor. indentified,																
Subdivision Corners																
No.																
1. Center ¼ Sec. Cor.																
2. North ¼-¼s N. W. qr.,																
3. East ¼-¼s N. W. qr.,																
4. South ¼-¼s N. W. qr.,																
5. West ¼-¼s N. W. qr.,																
6. Center ¼-¼s N. W. qr.,																
7. North ¼-¼s N. E. qr.,																
8. East ¼-¼s N. E. qr.,																
9. South ¼-¼s N. E. qr.,																
10. Center ¼-¼s N. E. qr.,																
11. East ¼-¼s S. E. qr.,																
12. South ¼-¼s S. E. qr.,																
13. West ¼-¼s S. E. qr.,																
14. Center ¼-¼s S. E. qr.,																
15. South ¼-¼s S. W. qr.,																
16. West ¼-¼s S. W. qr.,																
17. Center ¼-¼s S. W. qr.																

NAMES OF SWORN ASSISTANTS

CHAINMEN	FLAGMEN	AXMEN

No 313

~~No 314~~

Rockwell to Lumber Company
City of Elkhorn

Beginning at a point on the West line of Wisconsin Street in the City of Elkhorn, Wal. Co., Wis., 6 rods S. of the pt. of intersection of the W. line of said Wis. Street with the S. line of the right of way of the C. M. & St. P. R.R. Co. and said point being also the Southeast corner of one certain piece of land deeded by said grantor to Walter A. West. June 9, 1888, a record of which deed may be found in the Register of Deeds office in and for said County of Walworth in Volume 76 of Deeds on page 407, Thence S. along the W. line of said Wisconsin Street 10 rods, Thence West at right angles to the West line of said Wisconsin St. 16 rods to a line being the East line of Broad Street in said City of Elkhorn, produced South, Thence North on said line to the most southerly line of the Right of way of the above mentioned Ry. Co., Thence easterly along the South line of said right of way 8 rods to the Northwest corner of the piece deeded to said West as above mentioned; Thence South and East along the West and South side of the said piece to the place of beginning. Also beginning at the Northwest corner of this described piece to be deeded, being the pt. of intersection of the south line of the R.O.W of the above mentioned Ry. Co. with the East line of Broad Street produced South, Thence South on the West line of the above described piece 33 Ft., Thence in a Northwesterly direction to a pt. on the S. line of the above mentioned R.O.W. 90' Westerly of the place of beginning, Thence easterly on said South line to the place of beginning.

Surveyed by Wm Child Co

Recorded by Floyd S. Simmons Co
Feb. 28, 1934