

DESCRIPTION

Record of Survey.

OF SECTION, QUARTER SECTION AND QUARTER QUARTER SECTION CORNERS

no. 121

Explanation of survey made at the request of
Township of *Walworth* County, *Wisconsin*
as presented by the courses and distances on the following plat, and annexed field-notes of survey:
Established the center of the section at the point of intersection of STRAIGHT CENTER STREET
Established all quarter-quarter corners upon the section boundary at proportional distances between known
section and quarter section corners, according to the original field-notes of the Government survey.
Established all lost corners at proportionate distances between known corners, according to the original field
notes of the Government survey.
In making this survey I find at the northwest corner of said block 10, a stone set in place of a stake
driven in a former survey, and 72.4' South of this,
being on the west line of the block an iron stake in place
of a stake driven in the said survey, and I produce this
line to the south line of the block and find on the south
line of said block a distance of 349.5' to the west edge of
the sidewalk, and from the above mentioned stake at the
NW. corner of the block easterly along the south side of
said block 339.5' to the West line of said walk, which
distances being equally divided would give 5 lots of
69.9' in width on the South end or Center street and 67.9'
on the back or the alley; and I find that there has been
a survey made making a division in this manner.
The recorded plat of said Block no 10 shows each
of these 5 lots to be 1 chain or 66' in width on the south
or Center street, & 1 chain & 1 link or 66.66' on the alley
or a total distance on Center street of 330' & 333.3' on the
alley, giving an surplus of 6.2 on the alley & 19.5' on Center street.
I find on the West side of lot no. 4 an old fence part way
across said lot, producing the line of this fence south
to Center street I find it leaves the South end of lot
no 5 68.7' wide, and will strike the southerly side of the
barn at a point about 5' easterly of the southwest
corner, but did not ascertain the exact width it would

give said lot no. 5 on the alley. On the east side of
said lot no. 4 I find also a fence part way across the
lot and producing the line of this fence south to
center street I find it leaves the width of lot no 4 as
66.8' & this line produced to the alley is a point 334'
northeasterly of the northwest corner, and if an equal
division were to be made each of these lots (meaning
lots 4 & 5) would be 67' in width.

As can be readily seen by referring to the above
figures, that on the recorded plat the distance
across the rear end or along the alley should be
greater than that in front or along Center street, and
by referring to the measurements made both in my
survey of today and the survey previously made as
spoken of, the front line or along Center street
is much greater than that along the alley, which
is absolutely unaccountable to me at the present time.

William Childs
December 20, 1920
Recorded by Floyd S. Jensen
Jan 29, 1934

80 chains to 6 inches. The figures in red ink are the lengths of the lines as stated in the field-notes of the

Government survey.

Declination of the Magnetic Meridian from the True Meridian

Surveyed and sub-divided A. D. 1, in accordance

with the State Laws and Instructions of the Commissioner of the General Land office, and recorded on pages

of Register in the County Clerk's office.

Witness my hand this day of A. D. 1

SURVEYOR.

CHAINMEN

NAMES OF SWORN ASSISTANTS

FLAGMEN

AXMEN

no 122

16-1-16

Beginning at The Northwest corner of The Southwest quarter of Sec. 16, T1N, R16E, Thence East on The north line of said $\frac{1}{4}$ section 1315 feet more or less to The north East corner of The West half of said quarter section; Thence South on The East line of $N\frac{1}{2}$ 1286 feet to The centerline of The road; Thence Northwest along center of road ~~1274~~¹⁹⁷⁴ feet to place of beginning, containing 19.46 Acres.

Also beginning at point where road crosses East line of $N\frac{1}{2}$ of SW qr. S. on line ~~893.5~~⁷⁵⁴ feet to The railroad, Thence N.W. along railroad ~~712.5~~⁷⁵⁴ feet to Wright's land; North on line 754 feet to center of road; Thence SE 916 to place of beginning - containing 8.57 Acres of land.

William Childs
C.S.

Recorded by Lloyd S. Jensen
Jan 30, 1934 C.S.

no 123

Survey in (7-8-17-18) - 1-16

At corner of 7-8-17-18 found fence post for corner tipped over, set pine hub for corner. measured west 2.00, set flag at gr. Post between 7 & 8. found stake $37\frac{1}{2}$ links N. of E. gate post. Ran 2.00 west from this and then S 15.37 center of road, 40.41 line, east on sec. line 39.66 from corner to gr. post, found stake for $\frac{1}{8}$ post at 19.87 and .18 East of this is one link E. of E. face of fence. From West gr. post of 8 East 19.86 and find stake hole of stake set by former survey, from this North 2.76 fence on South of road, from this S 29.57 center of road 40.38 $\frac{1}{8}$ post.

William Childs
C.S.
Nov. 14, 1910

Recorded by Lloyd S. Jensen
Jan 30, 1934 C.S.