Record of Survey.

no. 121

Township Explanation of Survey made at the request of Interested parties as presented by the courses and distances on the following plat, and annexed field-notes of survey:

Established the center of the section at the point of intersection of STRAIGHT quarter lines.

Established all quarter-quarter corners upon the section boundary at proportional distances between known section and quarter section corners, according to the original field-notes of the Government survey.

Established all lost corners at proportionate distances between known corners, according to the original field notes of the Government survey.

John F Kinney Subd'n of Block No. 10 of the original plat of the recorded Village now City of Whitewater, Walworth County Wisconsin

In making this survey I find at the northwest corners of said Block 10, a stone set in place of a stake driven in a former survey, and 72.4' South of this, being on the west line of the Block an iron stake in place of a stake driven in the said survey, and I produce this line to the South line of the Block and find on the South line of said Block a distance of 349.5' to the west edge of the sidewalk, and from the above mentioned stone at the N.W. corner of the Block easterly along the north side of said Block 339.5' to the West line of said walk, which distances being equally divided would give 5 lots of 69.9' in width on the South end on Center street and 67.9' on the back on the alley; and I find that there has been a survey made making a division Var. This manner.

The recorded plat of said Block No 10 shows each of these 5 lots to be 1 chain or 66' in width on the south on Center street, & 1 chain & 1 link or 66.66' on the alley or a total distance on Center street of 330' & 333.3' on the alley, giving an overplus of 6.2 on the alley & 19.5 on Center Street.

I find on the West side of lot No. 4 an old fence part way across said lot, producing the line of this fence south to Center street I find it leaves the South end of lot No 5 68.7' wide, and will strike the Southerly side of the barn at a point about 5' easterly of the southwest corner, but did not ascertain the exact width it would give said lot No. 5 on the alley. On the east side of said lot No. 4 I find also a fence part way across the lot and producing the line of this fence south to center street I find it leaves the with of lot No 4 as 66.8' & this line produced to the alley is a point 334' northeasterly of the northwest corner, and if an equal division were to be made each of these lots (meaning lots 4&5) would be 67' in width.

As can be readily seen by referring to the above figures, that on the recorded plat the distance across the rear end or along the alley should be greater than that in front or along Center Street, and by referring to the measurements made both in my survey of today and the survey previously made as spoken of, the front line or along Center street is much greater than that along the alley, which is absolutely unaccountable to me at the present time.

William Childs
C.S.
December 20, 1920

Recorded by Floyd S. Jones C.S.
Jan 26, 1934

Plat of Section ..., Township ... North, Range ... of 4 Principal Meridian Scale 80 chains to 6 inches. The figures in red ink are the lengths of the lines as stated in the field-notes of the Government survey.

Declination of the Magnetic Meridian from the True Meridian ...

Surveyed and sub-divided ... A. D. 1 , in accordance with the State Laws and Instructions of the Commissioner of the General Land office, and recorded on pages ... of Register in the County Clerk's office.

Witness my hand this ... day of ... A. D. 1

... SURVEYOR.

DESCRIPTION

OF SECTION, QUARTER SECTION AND QUARTER QUARTER SECTION CORNERS

H. C. MILLER CO. MFG. STATIONERS, MILWAUKEE #15000

GOVERNMENT CORNERS	Bearing Trees	In. Dia.	Courses they bear	Links Distant	Bearing Trees	In. Dia.	Courses they bear	Links Distant	Bearing Trees	In. Dia.	Courses they bear	Links Distant	Bearing Trees	In. Dia.	Courses they bear	Links Distant
No.																
1. N. W. Sec. Cor. indentified,																
2. N. E. Sec. Cor. indentified,																
3. S. E. Sec. Cor. indentified,																
4. S. W. Sec. Cor. indentified,																
5. N. ¼ Sec. Cor. indentified,																
6. E. ¼ Sec. Cor. indentified,																
7. S. ¼ Sec. Cor. indentified,																
8. W. ¼ Sec. Cor. indentified,																
Subdivision Corners																
No.																
1. Center ¼ Sec. Cor.																
2. North ¼-⅛ N. W. qr.,																
3. East ¼-⅛ N. W. qr.,																
4. South ¼-⅛ N. W. qr.,																
5. West ¼-⅛ N. W. qr.,																
6. Center ¼-⅛ N. W. qr.,																
7. North ¼-⅛ N. E. qr.,																
8. East ¼-⅛ N. E. qr.,																
9. South ¼-⅛ N. E. qr.,																
10. Center ¼-⅛ N. E. qr.,																
11. East ¼-⅛ S. E. qr.,																
12. South ¼-⅛ S. E. qr.,																
13. West ¼-⅛ S. E. qr.,																
14. Center ¼-⅛ S. E. qr.,																
15. South ¼-⅛ S. W. qr.,																
16. West ¼-⅛ S. W. qr.,																
17. Center ¼-⅛ S. W. qr.																

CHAINMEN

NAMES OF SWORN ASSISTANTS

FLAGMEN	AXMEN

No 122 16-1-16

Beginning at the North west corner of the South west quarter of Sec. 16, T17, R16E; Thence East on the North line of said ¼ section 1315 feet more or less to the North East corner of the West half of said quarter section; Thence South on the East line of W½ 12 86 feet to the centerline of the road; Thence North west along center of road ~~1374~~ 1974 feet to place of beginning, containing 19.46 Acres.

Also beginning at point where road crosses East line of W½ of SW qr. S. on line ~~893.5~~ 893.5/754 feet to the railroad; Thence N.W. along railroad ~~732.5~~ 754 feet to Wrights land; North on line 754 feet to Center of road; Thence SE 916 to place of beginning - containing 8.57 Acres of land.

William Child
C.S.

Recorded by Floyd S. Jensen
Jan 30, 1934 C.S.

No 123 Survey in (7-8 & 17-18) - 1-16

At corner of 7-8-17-18 found fence post for corner tipped over, set pine tub for corner. measured west 2.00, set flag at qr. Post between 7 & 8. found stake 37⅕ links N. of E. gate post. Ran 2.00 west from this and then S 15.37 center of road, 40.41 line, east on sec. line 39.66 from corner to qr. post, found stake for ⅛ post at 19.87 and .18 East of this is one link E. of E. face of fence. From West qr. post of 8 East 19.86 and find stake hole of stake set by former survey, from this North 2.76 fence on South of road, from this S 29.57 center of road 40.38⅛ post.

William Child
C.S.
Nov. 14, 1910
Recorded by Floyd S. Jensen
C.S.
Jan 30, 1934