Record of Survey.

no 230 16-2-18

Township ..., North of Range ...of 4 Principal Meridian as presented by the courses and distances on the following plat, and annexed field-notes of survey:

Establishing the center of the section at the point of intersection of straight quarter lines.

Establishing all quarter quarter corners upon the section boundary and proportional distances between known section and quarter section corners according to the original field notes of the Government survey.

Establishing all lost corners at proportionate distances between known corners, according to the original field notes of the Government survey.

Copy of a portion of a survey made Nov. 16-17, 1885 on Sec. 9 & 16 T. 20 N. R. 2 E. by Mulvihill C.E. Wis. At the E. & W. Sec. Line Found Iron stake set and stump of Wit. tree 586 W 39 links and hole of stump N 82° E 7 links, From this stone, ran west 19.78 chains, and found stake set by The School Commissioners, for The 1/8 Sec. Corner of Sec. no. 16, and 19.90 chains found stake set, by James S. Tubbs (a former County Surveyor) for The 1/8 Section Corner, of Sec. no. 9; From the stake, at 19.78 chains West of As. Corner found stumps of Wit. tree, S 32° E, 19 links, drive new stake, for 1/8 Corner of Section no. 16 James Child, County Surveyor. Rec. in Vol. I P 469, The Survey spoken of, in which The 1/8 Sec. Cor. for Section no. 9, was set was made, march 7th 1861. by J. S. Tubbs, Then County Surveyor, and The Record of said survey may be found in Vol. no. I, of surveys, on Page 216, In This survey, Mr Tubbs makes The entire distance across The South side of The S. W. qr. of Sec. no. 9, 39.82 chains, and he sets The 1/8 Sec. Cor. At one half The distance, being 19.91 chains; and as The survey of my Father, in 1885 makes This distance 19.90 chains, it shows plainly That the school Commissioners Survey was in error, but which Survey must stand, so far as Section no. 16 goes, and The line of The fence running north will be, 12 links, (equalling 7.9 feet) west of The center of The Road running South, if The Road is laid out on The 1/8 Section line.

Var. Var. Var. Var. Var. Var. Var. Var. Var. Var. Var. Var.

C.H. Thorn June 8th, 1914
Wm Child C.S.

Plat of Section ..., Township ...North, Range ...4 Principal Meridian. Scale 80 chains to 6 inches. The figures in red ink are the lengths of the lines as stated in the field notes of the Government survey.

Declination of the Magnetic Meridian from the True Meridian ...

Recorded by Lloyd S. Jensen C.S.
Feb 19, 1934

Surveyed and sub-divided ..., in accordance with the State Laws and Instructions of the Commissioner of the General Land office, and recorded on pages ...of Register in the County Clerk's office.

Witness my hand this ...day of ...A. D. 1

...SURVEYOR.

DESCRIPTION

OF SECTION, QUARTER SECTION AND QUARTER QUARTER SECTION CORNERS

H. C. MILLER CO., MFG. STATIONERS, MILWAUKEE X15000

GOVERNMENT CORNERS	Bearing Trees	In. Dia.	Courses they bear	Links Distant	Bearing Trees	In. Dia.	Courses they bear	Links Distant	Bearing Trees	In. Dia.	Courses they bear	Links Distant	Bearing Trees	In. Dia.	Courses they bear	Links Distant
No.																
1. N. W. Sec. Cor. indentified,																
2. N. E. Sec. Cor. indentified,																
3. S. E. Sec. Cor. indentified,																
4. S. W. Sec. Cor. indentified,																
5. N. 1/4 Sec. Cor. indentified,																
6. E. 1/4 Sec. Cor. indentified,																
7. S. 1/4 Sec. Cor. indentified,																
W. 1/4 Sec. Cor. indentified,																
Subdivision Corners																
No.																
1. Center 1/4 Sec. Cor.																
2. North 1/4-1/8 N. W. qr.,																
3. East 1/4-1/8 N. W. qr.,																
4. South 1/4-1/8 N. W. qr.,																
5. West 1/4-1/8 N. W. qr.,																
6. Center 1/4-1/8 N. W. qr.,																
7. North 1/4-1/8 N. E. qr.,																
8. East 1/4-1/8 N. E. qr.,																
9. South 1/4-1/8 N. E. qr.,																
10. Center 1/4-1/8 N. E. qr.,																
11. East 1/4-1/8 S. E. qr.,																
12. South 1/4-1/8 S. E. qr.,																
13. West 1/4-1/8 S. E. qr.,																
14. Center 1/4-1/8 S. E. qr.,																
15. South 1/4-1/8 S. W. qr.,																
16. West 1/4-1/8 S. W. qr.,																
17. Center 1/4-1/8 S. W. qr.																

no. 231 27-2-18

Godfry, Batschelet & others

Began at Nort heast corner, found stake hole and roots of both trees. Set grote iron for stake, measured west at 59.97 east of tree given as 60.12 as qr. post and both trees are gone. d nt quarter post at 39.90 West of corner and 20.07 East of tree and in line and as corners is a line (gone d nt on at 79.63 giving 2 clks to bt line from north 73 links, N of) of trees and northeast corner to give 40.00 on West of quarter, at W. qr. post found one tree on west and roots S.E, set stake from There and run on 40.00 to corner, at 20.00 made point 1½ rods E of tree line being in line of fence from This post run E 79.79 to 1/8 post on East of N.E qr. which was established by running East line of qr. found E. line to be 40.25 and set 1/8 post at 20.12½ and in line being 16 links 5 and 4 links E of corner of fence, stake large post as E qr. post said to have been set in place of qr. post.

Surveyed by Wm Child C.S.
June 24, 1908

Recorded by Lloyd S. Jensen C.S.
Feb 14, 1934

NAMES OF SWORN ASSISTANTS

CHAINMEN	FLAGMEN	AXMEN

No 232 2-18

BLK. 26 - SPRINGFIELD

H. Noblet

Found pipe stake at Northeast corner and 66 feet South for corner of lot, at Northwest corner of lot 1 found corner post set in place of stake set by survey also at Southwest corner of lot 5 132 feet East of this last point make point and line from this point, hits East side of stake South of corner and goes to post at corner of block, from Northeast corner South 4 - 66 foot lots and 48.7 and make point, Then back 24 feet as per deed and set iron stake also for East corners of Lot 8 and 24.7 feet South of Southwest of 8, Giving Noblet 24.7 feet of the North side of lot.

Surveyed by Wm Child CS.
July 19, 1912

Recorded by Lloyd S. Jensen CS.
Feb. 15, 1934

No 232 16-2-18

F. J. Hillenbrand

Beginning at Northwest corner of Cemetery as fenced produced Southeast line of road 100' made point. Southeast at Right angles 165 feet to point 10 feet Southwest fence found point 219.78 to be at post, Ran on 115.5 feet more and set gas pipe stake 16 feet east of fence, turned Right Angles and ran East 165 feet Then Northeast parallel with road fence, an iron stake was driven 4 feet Northeast of the South corner and 4 feet Southwest of Northeast corner from point in line of fences at the Southwest corner of g. gs. using North fence as North, ran North 61° 40' E to iron pipe, The line of road is N 37° 36' E and the South end is S 52° - 23' E.

Surveyed by Wm Child CS.
April 24, 1908

Recorded by Lloyd S. Jensen
Feb. 16, 1934