

Record of Survey.

OF SECTION, QUARTER SECTION AND QUARTER QUARTER SECTION CORNERS

no 230

16-2-18

Township....., North of Range..... of 4 Principal Meridian

as presented by the courses and distances on the following plat, and annexed field-notes of survey:

Copy of a portion of a survey made Nov. 16-17, 1885 on Section No. 16, in the Town of Brown, Walworth Co., Wis. At the north E. Section corner found a line set and stump of W. 1/2 Sec. 58.6 N. 39 links and hole of stump in 82° E. 50 links, from this stone, ran west 19.78 chains, and found stake set by the School Commissioners, for the 1/8 Sec. Corner of Sec. No. 16, and 19.90 chains found stake set, by James S. Tubbs (a former County Surveyor) for the 1/8 Section Corner, of Sec. No. 9; From the stake, at 19.78 chains West of N. Corner found stump of W. 1/2 Sec. 532° E, 19 links, drive new stake, for 1/8 Corner of Section No. 16 James Child, County Surveyor. Rec. in Vol. I P 469, The Survey spoken of, in which the 1/8 Sec. Cor. for Section No. 9, was set was made, March 7th 1861, by J. S. Tubbs, then County Surveyor, and the Record of said survey may be found in Vol. No. I, of surveys, on Page 216, in this survey, Mr. Tubbs makes the entire distance across the South side of the S. W. qr. of Sec. No. 9, 39.82 chains, and he sets the 1/8 Sec. Cor. at one half the distance, being 19.91 chains; and as the survey of my father in 1885 makes this distance 19.90 chains, it shows plainly that the school Commissioners Survey was in error, but which Survey must stand, so far as Section No. 16 goes, and the line of the fence running north will be 12 links, (equalling 7.9 feet) west of the center of the Road running South, if the Road is laid out on the 1/8 Section line.

GOVERNMENT CORNERS

No. 1. N. W. Sec. Cor. identified, 2. N. E. Sec. Cor. identified, 3. S. E. Sec. Cor. identified, 4. S. W. Sec. Cor. identified, 5. N. 1/4 Sec. Cor. identified, 6. E. 1/4 Sec. Cor. identified, 7. S. 1/4 Sec. Cor. identified, 8. W. 1/4 Sec. Cor. identified, Subdivision Corners

No. 1. Center 1/4 Sec. Cor. 2. North 1/4-1/4s N. W. qr., 3. East 1/4-1/4s N. W. qr., 4. South 1/4-1/4s N. W. qr., 5. West 1/4-1/4s N. W. qr., 6. Center 1/4-1/4s N. W. qr., 7. North 1/4-1/4s N. E. qr., 8. East 1/4-1/4s N. E. qr., 9. South 1/4-1/4s N. E. qr., 10. Center 1/4-1/4s N. E. qr., 11. East 1/4-1/4s S. E. qr., 12. South 1/4-1/4s S. E. qr., 13. West 1/4-1/4s S. E. qr., 14. Center 1/4-1/4s S. E. qr., 15. South 1/4-1/4s S. W. qr., 16. West 1/4-1/4s S. W. qr., 17. Center 1/4-1/4s S. W. qr.

Plat of Section....., Township..... North, Range..... of 4 Principal Meridian Scale

80 chains to 6 inches. The figures in red ink are the lengths of the lines as stated in the field-notes of the

Government survey.

Declination of the Magnetic Meridian from the True Meridian.....

Surveyed and sub-divided....., in accordance

with the State Laws and Instructions of the Commissioner of the General Land office, and recorded on pages

..... of Register in the County Clerk's office.

Witness my hand this..... day of..... A. D. 1

..... SURVEYOR.

H. C. MILLER CO., MFG. STATIONERS, MILWAUKEE X15000

no. 231

27-2-18

Loddy, Batschelet & others
Began at North east corner found stake hole and roots of both trees. Set grove iron for stake, measured west at 59.97 east of tree given as 60.12 as gr. post and both trees are gone. Set quarter post at 39.90 West of corner and 20.07 East of tree and in line and as corner is a line 79.63 giving 2 lks to hit line from North 43 links N. of) of trees and northeast corner to give 40.00 on West of quarter, at W. gr. post found one tree on west and roots S. E., set stake from there and run on 40.00 to corner, at 20.00 made point 1 1/2 rods E of true line being in line of fence from this post ran E 79.79 to 1/8 post on East of N. E. gr. which was established by running East line of gr. found E. line to be 40.25 and set 1/8 post at 20.12 1/2 and in line being 16 links S and 4 links E of corner of fence. Stake large post as E gr. post said to have been set in place of gr. post.

Surveyed by Wm Child
June 24, 1908

Recorded by Lloyd S. Jensen
Feb 14, 1934

NAMES OF SWORN ASSISTANTS

CHAINMEN

FLAGMEN

AXMEN

no 232

2-18

BLK. 26 - SPRINGFIELD

H. Noblet

Found pipe stake at northeast corner and 66 feet South for corner of lot, at northwest corner of lot 1 find corner post set in place of stake set by survey also at Southwest corner of lot 5 132 feet East of This last point make point and line from This point, hits East side of stake South of corner and goes to post at corner of block, from northeast corner South 4-66 foot lots and 48.7 and make point, Then back 24 feet as per deed and set iron stake also for East corners of lot 8 and 24.7 feet South of Southwest of 8, giving Noblet 24.7 feet of The north side of lot.

Surveyed by Wm Child^{CS.}
July 19, 1912

Recorded by Lloyd S. Jensen^{CS.}
Feb. 15, 1934

no 233

16-2-18

F. J. Hillenbrand

Beginning at northwest corner of cemetery as fenced produced Southeast line of road 100' made point. Southeast at Right angles 165 feet to point 10 feet Southwest fence found point 219.78 to be at post, Ran on 115.5 feet more and set gas pipe stake 16 feet east of fence, turned Right angles and ran East 165 feet Then northeast parallel with road fence, an iron stake was driven 4 feet northeast of the South corner and 4 feet Southwest of northeast corner from point in line of fences at the Southwest corner of q. q. using north fence as north, ran north $61^{\circ} 40' E$ to iron pipe, The line of road is $273^{\circ} 36' E$ and the South end is $552^{\circ} 23' E$.

Surveyed by Wm Child^{CS.}
April 24, 1908

Recorded by Lloyd S. Jensen^{CS.}
Feb. 15, 1934