

PIN:
RXUP-230A

- = 1" IRON PIPE FOUND
- = 1"x24" IRON PIPE SET
- = 8" NAIL SET
- △ = P.K. MASONRY NAIL SET
- ▲ = COUNTY MONUMENT FOUND
- Y = HYDRANT
- ⊙ = WATER VALVE
- = POWER POLE
- ▣ = TELEPHONE PESTAL
- ▢ = ELECTRIC TRANSFORMER PAD
- ▣ = ELECTRIC METER
- ===== = PROPERTY LINE
- DPL = OVERHEAD POWER LINE
- E = BURIED ELECTRIC
- GAS = BURIED GAS
- V = WATER MAIN
- SS = SANITARY SEWER

Latitude: 42°-46'-17.46"
Longitude: 88°-24'-30.38"
(Per North American Datum of 1983/91)

Elevation: 945.0'
(Per National Geodetic Vertical Datum of 1929)

[illegible]

Commencing at the Southeast Corner of said Section 30; thence N00°-06'-45"E 311.31 feet along the East line of the SE1/4 of said Section 30; thence N89°-53'-15"W 371.68 feet; thence S14°-02'-02"E 25.00 feet; thence N75°-57'-58"E 30.00 feet to the point of beginning; thence S14°-02'-02"E 15.00 feet; thence S75°-57'-58"W 15.00 feet; thence S14°-02'-02"E 53.20 feet; thence N68°-04'-19"E 172.79 feet; thence N75°-17°-3"E 57.68 feet; thence N88°-47'-00"E 292.76 feet to the West Right-of-Way line of S.T.H. "120"; thence S05°-31'-42"W 20.14 feet along said West line; thence S88°-47'-00"W 286.03 feet; thence S75°-17°-31"W 54.05 feet; thence S68°-04'-19"W 194.49 feet; thence N14°-02'-02"W 76.16 feet; thence S75°-57'-58"W 15.00 feet; thence N14°-02'-02"W 15.00 feet; thence N75°-57'-58"E 50.00 feet to the point of beginning.


SITE BENCHMARK: (BM A) TOP NUT OF HYDRANT LOCATED
NORTH OF TOWER
ELEVATION = 966.82'

Craig A. Kneach
WISCONSIN REGISTERED LAND SURVEYOR
Craig A. Kneach, S-2333

 **AERO-METRIC**

Aero-Metric, Incorporated
Land Planning & Design Division
10-849-7708 800-472-5313 FAX (849-7708)
P.O. Box 10000 Madison Street CHILTON, WISCONSIN 53511

SITE SURVEY FOR SPRINT PCS



SHEET NO
1 OF 1

FILE NO.
K-27584

SPRINT PCS
SITE NO.
EAST TROY
GROUND BUILD
ML17XC812B

