

No. 73

Section 17

Township 1 North of Range 15 of 4 Principal Meridian

as presented by the courses and distances on the following plat, and annexed field-notes of survey:

Established the center of the section at the point of intersection of STRAIGHT quarter lines.

Established all quarter-quarter corners upon the section boundary at proportional distances between known section and quarter section corners, according to the original field-notes of the Government survey.

Established all lost corners at proportionate distances between known corners, according to the original field notes of the Government survey.

Survey for C. S. Suesmitch

Began at S. q. post as shown by Frank. North in center of road 2652 feet to line of fence West, made point in center of road as fenced N. at 2300 edge of marsh, 2652 corner of 4 fences, in line South at 600 South of woods, woods are about 150' wide, back 200 and runs to pt. at corner, 2021 corner, NE along fence at 530 West end of Willows, 968 corner at tree, fence post being 3 feet South, South along fence 787. to South line of section, as ran from South 1/4 post as shown to point of 3 fences as SW. cor. South 131 feet more center of road, NE along road 362 feet Section line. Began at SW. cor, North 634.5 corner of farm, from SW cor. East 1005 feet line of farm, from this line E 341 angle of road, 1665 beginning.

Plat of Section Township North, Range of 4 Principal Meridian Scale 80 chains to 6 inches. The figures in red ink are the lengths of the lines as stated in the field-notes of the Government survey.

Declination of the Magnetic Meridian from the True Meridian William Childs

Surveyed and sub-divided A. D. 1 in accordance with the State Laws and Instructions of the Commissioner of the General Land office, and recorded on pages

of Register in the County Clerk's office.

Witness my hand this day of Recorded by Lloyd S. Jensen Jan 11, 1934 County Surveyor.

OF SECTION, QUARTER SECTION AND QUARTER QUARTER SECTION CORNERS

GOVERNMENT CORNERS

- No. 1. N. W. Sec. Cor. identified,
- 2. N. E. Sec. Cor. identified,
- 3. S. E. Sec. Cor. identified,
- 4. S. W. Sec. Cor. identified,
- 5. N. 1/4 Sec. Cor. identified,
- 6. E. 1/4 Sec. Cor. identified,
- 7. S. 1/4 Sec. Cor. identified,
- 8. W. 1/4 Sec. Cor. identified,

Subdivision Corners

- No. 1. Center 1/4 Sec. Cor.
- 2. North 1/4-1/4s N. W. qr.,
- 3. East 1/4-1/4s N. W. qr.,
- 4. South 1/4-1/4s N. W. qr.,
- 5. West 1/4-1/4s N. W. qr.,
- 6. Center 1/4-1/4s N. W. qr.,
- 7. North 1/4-1/4s N. E. qr.,
- 8. East 1/4-1/4s N. E. qr.,
- 9. South 1/4-1/4s N. E. qr.,
- 10. Center 1/4-1/4s N. E. qr.,
- 11. East 1/4-1/4s S. E. qr.,
- 12. South 1/4-1/4s S. E. qr.,
- 13. West 1/4-1/4s S. E. qr.,
- 14. Center 1/4-1/4s S. E. qr.,
- 15. South 1/4-1/4s S. W. qr.,
- 16. West 1/4-1/4s S. W. qr.,
- 17. Center 1/4-1/4s S. W. qr.,

No. 74

Section 10-1-15

I accept fence attested to by Peters as being E & W. q. line at center and ran North 40.21 chains to q. post, found stake and stones, at NE. corner find 4 fences in good line and accept point as corner and ran South 40.11 chains to E q. post, accept fences as corner, at 20.05 1/2 chains set stake and ran West to point 20.10 1/2 chains South of North 1/4 Section post

Survey for E. A. Peters
Surveyed by William Childs

Recorded by Lloyd S. Jensen
Jan 11, 1934
County Surveyor.

NAMES OF SWORN ASSISTANTS

FLAGMEN

AXMEN

No. 75 Survey for F. J. Cowley
Section 18-T1N, R15E

At West q. post stake gone, not good signs of trees; from evidence ~~given~~ believe S. side of S. plank of bridge to be on line of Section and from this S 660 feet = 40 rods and set stake in center of road as fenced, from this E 2707 to fence attested to as gr. line at north q. post. find stake.

South 660 feet - 40 rods to pt. 1 ft. South of center of large post, ran line W. to pt., 40 rods South of corner stake, set at 82 rods from W.

Surveyed by William Childs
C.S.
Aug. 7, 1912

Recorded by Lloyd S. Jensen
County Surveyor.
Jan 11, 1934

No. 76 Section 4, T1N, R15E

Take point in line of fences south to West for NE. corner of Section! Taking fence South as South ran S 40° W 490 feet and set iron stake. Wit. by W.D. S 78°-45'E 31.2 feet, Hic. N 15° W 40.7'. Then South 76°-W. 200'; Wit. by W.D. S 86° E 50.8' Hic. N 44°-30'E 39.5', then S 44° E 268' set iron stake in line of road fence, Being 22' W. of light pole, 298' to center of road as fenced, N 50° E along center as fenced 179.5'. Then N 45°-50' W 30' set iron stake in line of fence being 13.5' E of light pole.

Surveyed by William Childs
C.S.
Jan 9, 1919

Recorded by Lloyd S. Jensen
County Surveyor
Jan 11, 1934