

DESCRIPTION

Record of Survey.

No. 116

4-4-15

Township....., North of Range.....of 4 Principal Meridian
as presented by the courses and distances on the following plat, and annexed field-notes of survey:

Established the center of the section at the point of intersection of STRAIGHT quarter lines.

Established all quarter-quarter corners upon the section boundary at proportional distances between known section and quarter section corners, according to the original field-notes of the Government survey.

Established all lost corners at proportionate distances between known corners, according to the original field notes of the Government survey.

Description of North piece

Lot 4 in Block no I of original plat.

All of that certain piece or parcel of land lying and being
in the city of Whitewater, Walworth County, Wisconsin, and
being also a part of Lot no. 4 in Block no. I of the recorded
plat of the resurvey of the village (now City) of Whitewater,
said plat being on record in the Register of Deeds office in and
for the said Walworth County in Vol. 3 of plats on pages 46 & 47
and more fully described as follows to wit:

Beginning at an iron stake on the east line of the said
lot no. 4 129.4 feet north of the northeast corner thereof;
Thence north on said east line to the Northeast corner of the
said lot no. 4; Thence west on the north line of said lot 4
to the Northwest corner thereof; thence south on the West line
of said lot to a pt. 129.4 feet north of the SW. corner of
said lot; thence easterly on a line parallel with the South
line of said lot no. 4 to the place of beginning.

Var.

Var. William Childs
C.S.

Var.

Recorded by Lloyd S. Jensen
C.S.
Jan. 29, 1934

Var.

Plat of Section....., Township.....North, Range.....of 4 Principal Meridian Scale
80 chains to 6 inches. The figures in red ink are the lengths of the lines as stated in the field-notes of the
Government survey.

Declination of the Magnetic Meridian from the True Meridian.....

Surveyed and sub-divided..... A. D. 1, in accordance

with the State Laws and Instructions of the Commissioner of the General Land office, and recorded on pages
of Register in the County Clerk's office.

Witness my hand this.....day of..... A. D. 1

SURVEYOR.

OF SECTION, QUARTER SECTION AND QUARTER QUARTER SECTION CORNERS

GOVERNMENT CORNERS	H. C. MILLER CO., MFG. STATIONERS, MILWAUKEE X19000										
	Bearing Trees	In. Dia.	Courses they bear	Links Distant	Bearing Trees	In. Dia.	Courses they bear	Links Distant	Bearing Trees	In. Dia.	Courses they bear

No. 1. N. W. Sec. Cor. identified, No 117 Description of South piece.

2. N. E. Sec. Cor. identified,

3. S. E. Sec. Cor. identified, All of that certain piece or parcel of land lying and being

4. S. W. Sec. Cor. identified in the city of Whitewater, Walworth Co., Wis. Also being a part

5. N. $\frac{1}{4}$ Sec. Cor. identified of lot 4 in Blk I of the plat of the resurvey of the city of Whitewater

6. E. $\frac{1}{4}$ Sec. Cor. identified Beginning at an iron stake on the East line of said lot 4,

7. S. $\frac{1}{4}$ Sec. Cor. identified of the SE. cor. of said lot. Said iron stake being the

8. W. $\frac{1}{4}$ Sec. Cor. identified Southeast corner of that certain parcel of land conveyed by

Eugene & Stella Roeman to J. G. & Mary C. Chamberlain. Handed

Subdivision corners No. Center $\frac{1}{4}$ Sec. of which conveyance is on record in the above mentioned

2. North $\frac{1}{4} \times \frac{1}{4}$ N. Reg. Register of Deeds office in Vol. 113 Page 471 of Deeds, & being

3. East $\frac{1}{4} \times \frac{1}{4}$ N. also the NE. corner of that certain parcel of land known in the

4. South $\frac{1}{4} \times \frac{1}{4}$ N. above mentioned deed of Roeman to Chamberlain as the Clapp

5. West $\frac{1}{4} \times \frac{1}{4}$ N. W. Livery Stable and also the NE. corner of that certain parcel of land

6. Center $\frac{1}{4} \times \frac{1}{4}$ N. W. conveyed by Jason Fries & Mary C. Chamberlain & J. G. Chamberlain

7. North $\frac{1}{4} \times \frac{1}{4}$ N. olda S. Lewey. The deed for the last mentioned conveyance is on

8. East $\frac{1}{4} \times \frac{1}{4}$ N. E. record in the Register of Deeds office in Vol. 113 of Deeds page

9. South $\frac{1}{4} \times \frac{1}{4}$ N. 378 qr. and subsequently conveyed to Cummings & Hickey, the deed

10. Center $\frac{1}{4} \times \frac{1}{4}$ N. E. of which conveyance is on record in the said register of

11. East $\frac{1}{4} \times \frac{1}{4}$ N. Deeds office in Vol. 163 of Deeds on page 366; Thence N. on the

12. South $\frac{1}{4} \times \frac{1}{4}$ N. E. line of said lot 4, 63.4 feet to an iron stake; Thence Westerly

13. West $\frac{1}{4} \times \frac{1}{4}$ N. E. line parallel with the N. line of the above mentioned

14. Center $\frac{1}{4} \times \frac{1}{4}$ S. E. of Cummings & Hickey lot to the W. line of said lot no. 4, a pt.

15. South $\frac{1}{4} \times \frac{1}{4}$ S. W. of the SW. corner of said lot 4; Thence S. on the N. line

16. West 63.4 feet to a pt. said pt. being on the North side of the wall

17. Center of the SW. qr. building now standing on the said Cummings & Hickey

lot; and being also on the S. line of the above described land

in deed of conveyance from Roeman to Chamberlain; Thence

easterly on the said line to the place of beginning

NAMES OF SWORN ASSISTANTS

William Childs
C.S.

CHAINMEN

FLAGMEN

AXMEN

William Childs
C.S.

Recorded by Lloyd S. Jensen

Jan. 29, 1934

No. 118

Block 4 of Berges Addition to City of Whitewater

This is to certify that I William Childs, County Surveyor of Walworth County Wisconsin have this day completed a survey of part of Block 4 of Berges Addition to the Village, now City of Whitewater. Which survey is as follows: At the northeast corner of said block 4 found remains of old post and drove iron stake in place.

At the northeast of Block 3 found stake set by former survey and from this survey stake ran South over iron stake at northeast corner of Block 4 to southeast corner. At southeast corner found remains of old post and drive stake being in line with stakes at northeast corners of Blks 3 and 4. From this last stake measured west 397.7 feet and find post hole in line fence North. Drive small stake in this post hole and from this stake measure west 198.8 feet to line of fence running North and 395.7 ft. and find post hole to be for corner of blk. Making the South side of said blk. 793.4 ft. From the northeast corner of said blk 4 west 395 feet and find post hole in line of fence running South. The line of this fence I believe to be the center of said blk. At the Southwest corner of blk 3 I find stake and stone set by former survey and 60 ft. South of this stake I find post hole which I believe to be the north line of blk, and from this point on line to northeast corner of blk. set good oak stake at 395 feet West of N.E. cor. for the N.W. cor. of lot 3 said blk. From this Oak stake measured East and set limestone at 82.8, 165.6 & 248.4 leaving 146.6 for last lot. Found East side of blk to be 513.6. Found point 256.8 to be on South side of ditch and in line of fence running West. Found West line of Blk. to be 522 feet. Found point 261 feet to be in line of fence East. Also found that line from this point to point in center of East line would hit fence post which fence post is in line of fence running North and South. I have already taken as being the center line North and south through said Blk. Making said fence post the true center of Blk. From this center measured East 396 feet to East line of Blk. Began at center and measured East 83.04 ft. and set stake, 166.08 and set fence post. The center of said fence post being the North and South line and 249.12 and made point leaving 146.9 for last lot. From this last mentioned point north to point on North side of Blk. 146.6 feet West of N.E. corner drove stake at 99 feet North, for Southwest corner of Bueuing piece. Also from point in center of east line of Blk. north 99 feet and set stake for southeast corner of Bueuing piece. A line from last mentioned stake went to stake set for Southwest corner of Bueuing piece strikes old fence post and fence post at Southwest corner of Bueuing piece as fenced. True Southwest corner being 1 foot west of corner post.

William Childs
C.S.Recorded by Lloyd S. Jensen
Jan. 29, 1934